

ESTA

**BSR E1.4-3 - 201x**  
**Entertainment Technology—Manually**  
**Operated Hoist Rigging Systems**

[Document number: Rig/2015-2022r7]

© 2017 ESTA . All rights reserved.

## **Notice and Disclaimer**

ESTA does not approve, inspect, or certify any installations, procedures, equipment or materials for compliance with codes, recommended practices or standards. Compliance with a ESTA standard or recommended practice, or an American National Standard developed by ESTA is the sole and exclusive responsibility of the manufacturer or provider and is entirely within their control and discretion. Any markings, identification or other claims of compliance do not constitute certification or approval of any type or nature whatsoever by ESTA.

ESTA neither guarantees nor warrants the accuracy or completeness of any information published herein and disclaim liability for any personal injury, property or other damage or injury of any nature whatsoever, whether special, indirect, consequential or compensatory, directly or indirectly resulting from the publication, use of, or reliance on this document.

In issuing and distributing this document, ESTA does not either (a) undertake to render professional or other services for or on behalf of any person or entity, or (b) undertake any duty to any person or entity with respect to this document or its contents. Anyone using this document should rely on his or her own independent judgment or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstance.

**Published by:**

ESTA

630 Ninth Avenue, Suite 609

New York, NY 10036 USA

Phone: 1-212-244-1505 Fax: 1-

212-244-1502

[standards@ESTA.org](mailto:standards@ESTA.org)<http://tsp.esta.org>

## The ESTA Technical Standards Program

The ESTA Technical Standards Program was created to serve the ESTA membership and the entertainment industry in technical standards related matters. The goal of the Program is to take a leading role regarding technology within the entertainment industry by creating recommended practices and standards, monitoring standards issues around the world on behalf of our members, and improving communications and safety within the industry. ESTA works closely with the technical standards efforts of other organizations within our industry, including USITT, ESTA, and VPLT, as well as representing the interests of ESTA members to ANSI, UL, and the NFPA. The Technical Standards Program is accredited by the American National Standards Institute.

The Technical Standards Council (TSC) was established by to oversee and coordinate the Technical Standards Program. Made up of individuals experienced in standards-making work from throughout our industry, the Committee approves all projects undertaken and assigns them to the appropriate working group. The Technical Standards Committee employs a Technical Standards Manager to coordinate the work of the Committee and its working groups as well as maintain a “Standards Watch” on behalf of members. Working groups include: Control Protocols, Electrical Power, Event Safety Floors, Fog and Smoke, Followspot Position, Photometrics, Rigging, and Stage Lifts.

ESTA encourages active participation in the Technical Standards Program. There are several ways to become involved. If you would like to become a member of an existing working group, as have over two hundred people, you must complete an application, which is available from the TSP website. Your application is subject to approval by the working group. Voters are required to attend meetings and to vote on letter ballots. Membership in ESTA is not a requirement, but there is a per person, per year participation fee. You can also become involved by requesting that the TSC develop a standard or a recommended practice in an area of concern to you.

The Rigging Working Group, which authored this [DRAFT] Standard, consists of a cross section of entertainment industry professionals representing a diversity of interests related to rigging and stage machinery for theatrical events. ESTA is committed to developing consensus-based standards and recommended practices in an open setting. Future Rigging Working Group projects will include updating this publication as changes in technology and experience warrant, as well as developing new standards and recommended practices for the benefit of the entertainment industry.

**Contact Information****Technical Standards Manager**

Karl G. Ruling  
ESTA  
630 Ninth Avenue, Suite 609  
New York, NY 10036  
Phone: 1-212-244-1505  
FAX: 1-212-244-1502  
[karl.ruling@esta.org](mailto:karl.ruling@esta.org)

**Assistant Technical Standards Manager**

Erin Grabe  
ESTA  
630 Ninth Avenue, Suite 609  
New York, NY 10036  
Phone: 1-212-244-1505  
FAX: 1-212-244-1502  
[erin.grabe@esta.org](mailto:erin.grabe@esta.org)

**Technical Standards Council Co-Chairs**

Mike Garl  
Mike Garl Consulting LLC  
Phone: 1-432  
[mike.garl@mikegarlconsulting.com](mailto:mike.garl@mikegarlconsulting.com)

Mike Wood  
Mike Wood Consulting LLC  
Phone: 1-512-288-4916  
Fax: 1-866-674-2179

**Rigging Working Group Co-Chairs**

Bill Sapsis  
Sapsis Rigging, Inc.  
Phone: 1-215-228-0888  
[bill@sapsis-rigging.com](mailto:bill@sapsis-rigging.com)

Chris Kaiser  
Syracuse Scenery & Stage Lighting, Inc.  
Phone: 1-315-453-8096  
[ckaiser@syracusescenery.com](mailto:ckaiser@syracusescenery.com)

**Rigging Working Group Voting Members**

[Insert list of working group voting members, current at the time of document approval]

**Table of Contents**

Notice and Disclaimer.....	i
Foreword.....	vi
Reference standards organizations.....	vi
1 Scope.....	1
1.1 General .....	1
1.2 Building Structures.....	1
1.3 Annex note references.....	1
1.4 Exclusions.....	1
1.4.2 Powered rigging.....	1
1.4.3 Other rigging.....	1
1.5 Intent.....	1
1.6 Alternative designs .....	1
2 References.....	1
3 Definitions.....	2
4 Risk assessment and risk reduction.....	4
5 General design requirements.....	4
6 Mechanical design .....	5
6.1 General requirements .....	5
6.2 Power transmission components.....	6
6.2.1 Design factors .....	6
6.2.2 Load-securing devices.....	6
6.2.3 Drive sprockets.....	6
6.2.4 Wire rope drums* (See Annex note.).....	6
6.3 Hoist frames and static load bearing components.....	7
6.4 Manual hoist drive augmentation.....	7
7 Ancillary and tension load path components.....	7
7.1 Clew systems.....	7
7.2.1 General.....	8
7.2.2 Lifting media terminations.....	8

7.4 Load carrying devices..... 9

8 Basic functional, safety, and operational requirements..... 9

9 Labeling, marking, and signage..... 9

10 Installation..... 10

11 Inspection and testing ..... 10

    11.1 General requirements..... 10

    11.2 Inspection procedures..... 11

    11.3 Testing procedures..... 11

    11.4 Frequency of inspections..... 11

    11.5 Documentation..... 11

Annex A..... 12

    A6.1.3..... 12

    A.6.1.4..... 12

    A.6.1.5..... 12

    A.6.2.4..... 12

    A6.2.4.7..... 13

    A.7.1.2 ..... 13

    A.8.1..... 13

    A.8.3..... 13

## Foreword

Prior to final approval of ANSI E1.4-2009, no American National Standard had addressed safety of counterweight rigging systems for the entertainment industry. The first documented recognition that safety standards were needed occurred in the early 1960's, when the United States Institute for Theatre Technology (USITT) established its Codes Commission to monitor and report on development of national codes that might be applicable to the entertainment industry. This commission eventually expanded its scope to include the Health & Safety subcommittee. By 1965 USITT had acknowledged that industry standards were necessary to ensure safety in the industry. The first formal, documented effort to accomplish this goal spawned from a Theatre Architecture Commission panel discussion at the 1980 USITT Conference in Kansas City, Missouri. In order to improve the level of safety and to establish a minimum standard for the manufacture of rigging equipment for use in the entertainment industry, the United States Institute for Theatre Technology, Inc. (USITT) established its Rigging and Stage Machinery Standards Committee, with the mission of creating a comprehensive set of standards for this purpose. To further this goal, sub-committees were established to write standards in several areas that combine to achieve a set of standards to fully describe the mechanical equipment used in theatres. This document is an evolution of work first started by separate sub-committees for Manual Counterweight Flying Systems and for Rope and Sandbag Flying Systems. The resulting efforts were combined to form the basis of this document.

It was originally intended that this document be accepted as a standard of USITT and that it ultimately become an American National Standard. In order for the latter to happen, the USITT draft document was turned over to ESTA's Technical Standards Program (now the ESTA Technical Standards Program). It has been further developed by the Rigging Working Group within that program. Members of the Rigging Working Group include appropriately qualified people who represent the broader industry of people who specify, manufacture, sell, and use this equipment, so that all interests are recognized and the standards represent a great depth of knowledge and experience in regards to the equipment.

In 2014, the RWG approved expansion of E1.4's scope, into a suite of related standards, which are currently in development. This draft represents the 3<sup>rd</sup> installment to a planned suite of 4.

This document establishes minimum standards for equipment. However, the proper installation and operation of this equipment are equally important. Equipment shall be installed, operated and maintained under the supervision of a competent person. Further, the selection of the proper equipment for any application shall be entrusted only to experienced personnel with the proper knowledge and training to recognize and understand all of the hazards and functional requirements involved in the particular installation.

This standard represents equipment manufactured under the constraints of current technology. It is not intended to restrict further developments or enhancements. Revisions of this standard will be considered by the committee in the light of further advances in technology, changes in entertainment requirements, and operating practices. Future revisions will not imply that previous editions of the standard were inadequate. Nor is it the intention of this standard to suggest that equipment manufactured before the creation of this standard is inherently inadequate.

## Reference standards organizations

The following standards organizations have developed specific standards documents that may pertain to certain normative requirements of this standard. It is not intended to identify all such organizations, or their respective standards, nor is it intended to imply that compliance with any such standard constitutes an exemption from any legal, jurisdictional, or OSHA-related safety requirements that may exist.

AISI - American Iron and Steel Institute, Inc.  
ANSI - American National Standards Institute  
ASME - American Society of Mechanical Engineers

- ASTM - American Society for Testing and Materials
- AWS - American Welding Society
- ESTA - Entertainment Services and Technology Association
- IFI - Industrial Fasteners Institute
- ISO - International Organization for Standardization
- NACM - National Association of Chain Manufacturers
- SAE - Society of Automotive Engineers



## 1 Scope

### 1.1 General

This standard applies to permanently installed, manually operated hoists used as part of rigging systems for raising, lowering, and suspension of scenery, properties, lighting, and similar loads. This standard establishes requirements for the design, manufacture, installation, inspection, and maintenance of manually operated hoist systems for lifting and suspension of loads for performance, presentation, and theatrical production.

### 1.2 Building Structures

This standard applies to the mechanical hoist and rigging hardware only, not to the structure from which it is supported. While not part of this standard, the ability of the building structure to support the intended loads shall be considered in the design and application of rigging systems.

### 1.3 Annex note references

This document uses annex notes to provide additional reference information about certain specific section requirements, concepts, or intent. Subject matter with a corresponding annex note reference is identified by the asterisk (\*) symbol and the text "See Annex note;" the associated reference text is found in the Annex A section, identified with the referring text section number, e.g. an Annex Note to section 3.2 will be identified in the annex section as A.3.2.

### 1.4 Exclusions

#### 1.4.1 Performer flying

This standard does not apply to performer flying, or to raising or lowering people.

#### 1.4.2 Powered rigging

This standard does not apply to any equipment used in permanently powered rigging systems, nor to any manually operated system temporarily operated using powered rigging components. Powered rigging equipment shall conform to the applicable requirements of ANSI E1.6.

#### 1.4.3 Other rigging

This standard does not apply to E1 Entertainment Technology equipment covered under the scope of other existing standards.

### 1.5 Intent

The purpose of this standard is to establish minimum performance requirements for manually operated hoists used in rigging systems. This standard establishes safeguards to public health, safety and general welfare with the intent to minimize hazards associated with Manually Operated Rigging Systems.

### 1.6 Alternative designs

This standard is not intended to prevent or limit alternative designs, materials, or technology. Alternative designs, materials or technology shall comply with the intent of this standard, and with the requirements of any other standard deemed applicable by a qualified person.

## 2 References

All equipment shall be manufactured and installed to comply with this standard and any applicable codes or jurisdictional regulations where the requirements of such codes or regulations are more stringent.

The following documents are referenced. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document, including any amendments, shall apply.

ANSI/ASME B29.4 2002 Roller Load Chains for Overhead Hoists

ANSI E1.2 2006 Design, Manufacture and Use of Aluminum Trusses and Towers

ANSI Z535 2006-

- 1, Safety Color Code
- 2, Environmental and Facility Safety Signs
- 3, Criteria for Safety Symbols
- 4, Product Safety Signs and Labels
- 6, Product Safety Information re Product Manuals, Instruction and Other Collateral Materials

### 3 Definitions

**3.1 Batten:** A pipe, tube, or other singular structural shape that is secured to the lift lines for the purpose of connecting loads to the counterweight system.

**3.2 Block:** An assembly of one or more sheaves in a housing designed to support one or more lines to allow a change of direction.

**3.3 Clew:** A device with multiple holes used to connect several lift lines into a common line.

**3.4 Competent person:** A person who is capable of identifying existing and predictable hazards in the workplace, and who is authorized to take prompt corrective measures to eliminate them.

**3.5 Design factor:** (a) A ratio of the design load limit to the yield strength of a material or component; (b) A ratio of the design load limit to the ultimate strength of a material or component where the material does not plastically deform prior to failure.

**3.6 Design load:** The maximum anticipated load that will govern design conditions.

**3.7 Guide system:** Components and assemblies used to guide a clew, including components attached to the clew specifically for such purpose, and including clew travel- limiting components such as stop.

**3.8 Hand winch:** See **3.18 Manually operated hoist.**

**3.9 Haul line(s):** The primary tension load path element connecting the hoist to the other rigging components.

**3.10 Hoist system:** See **3.15 Line set.**

**3.11 Installer:** The person or organization that is responsible for the installation of the rigging equipment.

**3.12 Lift line:** Any lifting media reeved through head blocks and loft blocks, and attached to a load. Lift lines operate singly, as spot lines, or in "sets" of several lift lines working together to support a load or a batten.

**3.13 Lifting medium:** the load-carrying element that is driven by the hoist to move the load (e.g. wire rope, roller chain).

**3.14 Limits of use:** the parameters under which the system is designed to operate (e.g. working load limit, speed of movement, duty cycle, environmental conditions, user skill level, availability of maintenance).

**3.15 Line set:** A system of multiple lift lines, operated together to raise, lower, or suspend a load; All of the mechanical, component subsystems required for supporting, positioning, and operating those lift lines as a system.

- 3.16 Load carrying device:** the component(s) of the hoist system that connect a suspended load to the lifting media (e.g. batten, truss, and hook).
- 3.17 Load securing device:** a mechanical device that prevents unintentional movement in the hoist system.
- 3.18 Manually operated hoist:** A hoist primarily intended and designed to be hand-operated.
- 3.19 Pile-on drum:** drum in which the individual lifting media are confined in separate winding chambers so that the lifting media winds in concentric layers.
- 3.20 Pitch diameter:** The diameter of a sheave or drum measured to the centerline of its groove.
- 3.21 Power transmission system:** the components within the hoist that create, transfer, support, or dissipate mechanical force and motion (e.g. gears, shafts, clutches, couplings, bearings).
- 3.22 Qualified person:** A person who by possession of a recognized degree or certificate of professional standing, or who by extensive knowledge, training, and experience, has successfully demonstrated the ability to solve or resolve problems relating to the subject matter and work.
- 3.23 Reeve:** To pass a rope over the sheaves in a block or a system of blocks.
- 3.24 Reverse bend:** A condition where a line is reeved so that it bends in opposing directions, over two or more sheaves.
- 3.25 Rigging:** General term for arrangements of hardware and systems for the raising, lowering, and suspension of scenery, properties, lighting, and similar loads used in performance venues.
- 3.26 Risk:** combination of the probability of occurrence of harm and the severity of that harm.
- 3.27 Risk assessment (RA):** the process of identifying, evaluating, and quantifying the potentially hazardous conditions, severity, and probability of occurrence of harm.
- 3.28 Risk reduction (RR):** mitigation of risk created by hazardous conditions.
- 3.29 Shall:** A term used in this standard to indicate that an action is mandatory.
- 3.30 Should:** A term used in this standard to indicate that an action is recommended under most conditions, but is not mandatory
- 3.31 Tension load path:** The path of tension-only load that follows the axis of the rope or wire rope lift lines, including all connections and terminations along this path.
- 3.32 Ultimate load carrying capacity:** the maximum load an assembly may support without failure or permanent deformation, as determined by nationally recognized construction standards appropriate for the given material.
- 3.33 Wire guide:** Tensioned wire ropes used to guide the path of counterweight arbors or clews.
- 3.34 Working load limit:** The maximum recommended capacity of a component or system, during normal operating conditions as determined by the manufacturer or a qualified person.

## **4 Risk assessment and risk reduction**

**4.1** Risk assessment and risk reduction (RA/RR) for a hoist or hoist system shall be performed throughout design, fabrication, installation, and testing. Risk assessment and risk reduction shall be performed when hoists or hoist systems are modified.

**4.2** Risk assessment and risk reduction preferably shall be performed by a group of two or more competent persons. When the risk assessment and risk reduction is completed by a single individual, that individual shall be a qualified person.

**4.3** The group or person performing the risk assessment and risk reduction shall determine the acceptable level of residual risk.

**4.4** The group or person conducting a risk assessment and risk reduction shall:

**4.4.1** Identify and document the limits of use;

**4.4.2** Identify and document the tasks anticipated throughout the life of the system;

**4.4.3** Identify and document the hazards associated with each task;

**4.4.4** Estimate the severity of harm associated with exposure to the hazard;

**4.4.5** Estimate the probability of occurrence of harm from the hazard;

**4.4.6** Identify the risk by considering the severity and probability of harm;

**4.4.7** Evaluate the risk associated with each hazard to determine if the risk is acceptable;

**4.4.8** Take measures to reduce unacceptable risks;

**4.4.9** Determine whether new or additional hazards have been introduced, or if the level of existing risks have been changed;

**4.4.10** Repeat this process until an acceptable level of residual risk is achieved; and

**4.4.11** Documentation of the risk assessment and risk reduction shall include the mitigating actions taken for each hazard and the resulting reduction in risk.

## **5 General design requirements**

**5.1** Hoist systems shall be designed by qualified persons.

**5.2** Hoist systems shall incorporate all aspects of mechanical requirements herein unless otherwise determined by the risk assessment and risk reduction.

**5.3** Hoist systems shall be designed for use in the anticipated environmental and operating conditions. These conditions shall be included in the limits of use.

**5.4** All components of the system shall be used in accordance with manufacturers' recommendations.

**5.5** The distribution of loads in a multiple line hoist system, or between hoists in a multiple hoist system, shall be assessed.

**5.6** Variations caused by the uneven application of load, deflections of lifted objects, deflection of supporting structure and/or hoist system supports shall be assessed.

**5.7** Hoist systems shall be free from vibration that threatens the integrity or functionality of the hoist under normal operating conditions.

**5.8** Hoist systems shall be protected against uncontrolled speed and unintentional movements.

**5.9** Hoist systems shall be designed for anticipated duty cycles and product life.

**5.10** Where the supplier of any component or sub-assembly of the hoist system is not responsible for the entire hoist system, the system designer shall specify the safety requirements for the component or subassembly.

**5.11** Design of components not specifically referenced within this document shall be reviewed according to applicable standards. In the absence of an applicable standard, the designer shall apply generally accepted engineering principles.

**5.12** Design of the hoist shall anticipate a reasonable amount of force a user would be expected to exert upon the control handle(s).

## **6 Mechanical design**

### **6.1 General requirements**

A qualified person shall determine or approve design factors for all equipment not included in the tension load path. Unless modified by other sections of this document, other codes listed, or governing bodies with jurisdiction over a particular facility, the factors listed in ANSI E1.4-2014 shall be used as a minimum performance guideline for tension load path equipment, unless a professional engineer determines that lower values are permitted.

**6.1.1** Unless specifically addressed herein, all manual rigging equipment shall comply with the relevant requirements of ANSI E1.4 - 2014 Manual Counterweight Rigging Systems. Component assemblies shall be designed, engineered, and manufactured to withstand all design loads without deformation or damage to components and shall meet the requirements of section 6.2.1 Design Factors.

**6.1.2** The hoist system shall be capable of moving the lifted load from a static condition and returning it to the static state, maintaining control throughout the operation.

**6.1.3** Design loads shall be considered in determining the loads applied to the building structure.\* (See Annex note.)

**6.1.4** Housings and mounting components shall use materials having ductile properties that will deform plastically without fracturing.\* (See Annex note.)

**6.1.5** Strength, material, quality and marking requirements for externally-threaded fasteners shall not be less than SAE J429 Grade 5 or ISO R898 Class 8.8 rating. Bolts in tension shall have nuts of equivalent rating. Fasteners shall be self-locking, or secured by alternate means to prevent loosening. Fasteners shall be installed in accordance with manufacturer's instructions. Attachments made through slotted, elongated, or over-sized holes (more than 1/16" over the fastener diameter), shall use flat washers.\* (See Annex note.)

**6.1.6** All components shall resist unintentional loosening.

**6.1.7** Welding shall be in accordance with current AWS standards.

## **6.2 Power transmission components**

### **6.2.1 Design factors**

For power transmission components that have a manufacturer's recommended load rating, the design load shall not exceed the load rating at a minimum Service Factor of 1.0. Power transmission components without manufacturer's load ratings shall be designed so that stresses due to the design loads do not exceed the following:

**6.2.1.1** Shear stresses - 33% of the yield strength; and

**6.2.1.2** Bearing (contact) stresses - 63% of the yield strength

**6.2.1.3** For power transmission components for which the manufacturer has recommended load ratings, the load shall not be released upon application of the design load. Power transmission components without a manufacturer's load rating shall be designed such that the design load does not exceed the yield strength of the component.

### **6.2.2 Load-securing devices**

**6.2.2.1** Hoists shall include at least two independently functioning load-securing devices.

**6.2.2.2** At least one of the load-securing devices shall have constant engagement or automatically engage when input force is removed.

**6.2.2.3** Each load-securing device shall be capable of holding 125% of the design load.

**6.2.2.4** A low back-driving efficiency gear reducer may be used in place of a load-securing device only when risk assessment and risk reduction mitigates hazards associated with descent of the load as a result of release or failure of the other load-securing device.

**6.2.2.5** It shall be possible to test the effectiveness of each load-securing device separately. Single use devices shall be acceptable if they have proven reliability based upon independently verified manufacturer testing.

### **6.2.3 Drive sprockets**

**6.2.3.1** This section applies to sprockets that transmit power to the lifting media.

**6.2.3.2** Roller chain sprockets in the power transmission system shall have a minimum of 12 teeth, and a minimum of 120 degrees of the chain shall be form-locked around the sprocket.

**6.2.3.3** A mechanism shall be included to prevent the chain from disengaging the sprocket teeth.

### **6.2.4 Wire rope drums\* (See Annex note.)**

**6.2.4.1** Wire rope drums shall be designed to take up wire rope in a defined and repeatable manner.

**6.2.4.2** Grooves on wire rope drums shall be sized as recommended by the wire rope manufacturer.

**6.2.4.3** Drum pitch diameters shall be sized as recommended by the wire rope manufacturer. Smaller pitch diameters shall be acceptable with risk assessment including any reductions in capacity, travel speed, travel distance, duty cycle and/ or lifecycle of wire rope or other components.

**6.2.4.4** Drums shall resist tread pressures imposed by the wire rope.

**6.2.4.5** Drums may be grooved or non grooved. Drums shall be designed and installed to even lay, tight wrapping and stacking of the wire rope.

**6.2.4.6** The maximum allowable fleet angle for a grooved drum shall be two (2) degrees. The maximum allowable fleet angle for a smooth drum shall be one and one half (1.5) degrees.

**6.2.4.7** When pile-on drums are used, each wire rope shall have its own winding chamber that ensures the rope is layered in such a manner that the rope centerlines are aligned. Reduced capacity of wire rope due to pile on condition shall be considered in design.\* (See Annex note.)

**6.2.4.8** The attachment of the wire rope to the drum shall remain secure for a load at least 80% of the wire rope's minimum breaking strength. This shall be accomplished by end termination alone, or by including the friction from the minimum turns of wire rope on the drum.

**6.2.4.9** When clamps are used to attach the wire rope to the drum, it shall be ensured that a single failure of the attachment method (e.g. screw) does not lead to the failure of the connection.

### **6.3 Hoist frames and static load bearing components**

**6.3.1** Hoist frames and static load bearing components shall be designed such that the design load does not exceed 50% of the yield strength of the material or 33% of the ultimate load carrying capacity.

**6.3.2** Deflection of load bearing components shall not be detrimental to hoist operation.

## **7 Ancillary and tension load path components.**

### **7.1 Clew systems**

**7.1.1** Clews shall be used where multiple lift lines are connected to fewer haul lines.

**7.1.2** Clews shall be guided or restrained to prevent fouling and twisting of the lines during operation. Clew guides may be wire, or rigid members. Other clew guiding methods shall be permitted.\* (See Annex note.)

**7.1.2.1** Clew systems shall be designed to withstand anticipated loads.

**7.1.2.2** Clew systems may be oriented in any direction. Non-vertical clew guide systems shall be supported as determined by a qualified person.

**7.1.2.3** Clew systems shall permit full intended travel of the batten or load.

**7.1.2.4** Wire guide attachments shall be located to permit clew travel without excessive deflection of the clew or its guides. A load-rated tension adjustment device shall be incorporated into the assembly, and shall be fixed in position after final adjustments are made.

**7.1.2.4.1** Wire guide attachment points shall be designed to accept the loads imposed by both tension in the guide wires and any loads due to sway of the clew during operation. A registered design professional shall evaluate anticipated guide wire loads to the existing structure.

**7.1.2.4.2** The minimum spacing between adjacent clews shall be such that clew system components cannot come into contact with each other under normal operating conditions.

### **7.2 Lifting media**

## **7.2.1 General**

**7.2.1.1** Minimum tensile strength of lifting media shall meet or exceed eight (8) times the design load.

**7.2.1.2** The minimum tensile strength shall include termination efficiency and other applicable strength reduction factors.

**7.2.1.3** In multiple line hoist systems, lifting media shall have a method of length adjustment.

**7.2.1.4** Lifting media shall not contact any part of the building structure, adjacent systems, or other equipment not intended for contact.

**7.2.1.5** In cases where inspection is not possible, risk analysis and risk reduction shall address means to mitigate this additional risk.

## **7.2.2 Lifting media terminations**

**7.2.2.1** Termination hardware shall be load rated and shall have a minimum tensile strength not less than 80% of the minimum tensile strength of the lifting media.

**7.2.2.2** Shackles, wire rope clips, eyebolts, eye nuts, and turnbuckles shall be of forged steel or equivalent construction. Malleable wire rope clips shall not be permitted.

**7.2.2.3** Turnbuckles shall be secured after adjustment to prevent turnbuckle body rotation.

**7.2.2.4** Screw pin shackles and turnbuckles with screw pin jaws shall be secured to prevent pin rotation.

**7.2.2.5** Thimbles shall be sized in accordance with the wire rope diameter.

### **7.2.2.6 Wire rope**

**7.2.2.6.1** The grade and construction of wire rope shall be appropriate for the intended use.

**7.2.2.6.2** Anticipated duty cycle and detrimental conditions such as reverse bending shall be factored into the selection of wire rope.

## **7.2.3 Other lifting media**

Other lifting media shall be permitted provided the manufacturer approves it for this use.

## **7.3 Blocks**

Blocks shall conform to the requirements of ANSI E1.4-2014 [ANSI E1.4-1]

## **7.4 Load carrying devices**

**7.4.1** Load carrying devices shall be selected so that the design load does not exceed 75% of the available strength permitted by published design standards applicable to the material.

**7.4.2** Battens or their equivalents shall be designed so that the calculated deflection in the span between two suspension points due to the design load uniformly distributed along the entire length of the batten is not greater than the length of the span divided by 180.

**7.4.3** Aluminum trussing shall meet the requirements of ANSI E1.2-2012.



## **8 Basic functional, safety, and operational requirements**

**8.1** All rigging installations shall include an operations and maintenance manual (“systems manual”) for the system, describing its limits of use. All unique elements of the particular system shall be identified and documented. The systems manual shall include final print drawings, applicable maintenance requirements, servicing guidelines, and a listing of component working load limits. Manuals shall include inspection requirements.\* (See Annex note.)

**8.1.1** System manuals shall include a supplemental maintenance log providing a place to record inspections, modifications and repairs to the system, and identifying the person(s) performing such actions.

**8.1.2** System manuals shall be made available upon request. The operations portion of the system manual shall be readily accessible to all users of the system.

**8.1.3** The operation of the system shall be clearly described and include comprehensive operator instructions.

**8.2** The maintenance section shall include recommendations for inspection, testing, and maintenance of the system.

**8.2.1** Systems shall be maintained under the supervision of a qualified person.

**8.2.2** Manually operated hoist systems shall be maintained in accordance with the System Manual.

**8.2.3** Replacement components and hardware shall be of equivalent grade or rating as the originals.

**8.2.4** Modifications or alterations shall be performed under supervision of a qualified person according to the provisions of this standard.

## **9 Labeling, marking, and signage**

**9.1** Labeling and signage shall comply with the requirements of the following standards, where such requirements can be implemented with rigging components, assemblies, and systems:

**9.1.1** ANSI Z535.1-2006, Safety Color Code

**9.1.2** ANSI Z535.2-2006, Environmental and Facility Safety Sign

**9.1.3** ANSI Z535.3-2006, Criteria for Safety Symbols

**9.1.4** ANSI Z535.4-2007, Product Safety Signs and Labels

**9.2** The hoist shall have a label affixed indicating the manufacturer's working load limit.

**9.3** Hoist systems shall be marked with their working load limit.

**9.4** Signage or label(s) shall indicate both WLL point load and WLL uniformly distributed load (UDL) of the load-carrying device for each hoist system.

**9.5** The lifting media size and type shall be clearly indicated either by a label affixed to the hoist or a sign or label directing the maintenance personnel to the system manual.

**9.6** The manufacturer's name or grade reference mark shall be permanently displayed on hardware. Or, where permanent labeling or marking of individual components is impractical; the load, manufacturer, or grade reference information shall be indicated in the system manual.

**9.7** Signage shall be placed in clearly visible, accessible location(s).

**9.8** Signage shall state that operation of the hoist system shall be restricted to authorized persons.

**9.9** Signage shall list the contact information for the supplier of the system.

## **10 Installation**

Systems shall be installed under the supervision of a qualified person. All components shall be installed in accordance with the system designer's recommendations.

## **11 Inspection and testing**

### **11.1 General requirements**

**11.1.1** Design and operating criteria of the rigging system shall be established or confirmed prior to inspection or testing.

**11.1.2** Inspection and testing shall verify that all system components and connections are present in the system, and that they comply with the design and operating criteria.

**11.1.3** Tests shall be non-destructive.

**11.1.4** The system designer's recommendations for inspection and maintenance shall be followed unless they are less stringent than the requirements herein.

**11.1.5** Inspection and testing shall be performed by a qualified person.

**11.1.6** Systems shall be inspected annually, or on a more frequent schedule, as determined by a qualified person.

**11.1.7** Systems shall be tested after installation, mishap, repair, or modification.

**11.1.8** Deficiencies discovered during inspection or testing shall be repaired under the supervision of a qualified person prior to returning the system to operation.

**11.1.9** Test failure shall result in corrections and retesting until the system passes the test.

### **11.2 Inspection procedures**

**11.2.1** Components of the hoist system shall be visually inspected for wear and damage.

**11.2.2** Each hoist or hoist system shall be operated through its full range of travel and speeds. Unusual noises, motions, or other issues shall be reported and resolved.

**11.2.3** All relevant Inspection requirements shall comply with ANSI E1.4-2014.

### **11.3 Testing procedures**

**11.3.1** The hoist system shall be inspected.

**11.3.2** Each hoist or hoist system shall undergo a static load test at 125% of the WLL.

**11.3.3** Any additional tests required by the designer or manufacturer shall be conducted.

**11.4 Frequency of inspections**

Installed systems shall be inspected annually or more frequently, as determined by a qualified person.

**11.5 Documentation**

**11.5.1** Inspection reports and test reports shall include the name of the inspector, the location of the equipment, and the date of the inspection. Reports shall be signed by the inspector.

**11.5.2** Test reports shall include documentation of the test procedures and the results of the tests.

**11.5.3** Inspection reports and test reports shall be placed in a system log.\* (See Annex note.)

## Annex A

This annex contains informative notes that are not part of the normative requirements of the standard.

### A6.1.3

Even though not within the scope of this standard, consideration of the loads applied to the building structure are important, especially when there may be an increase in loads due to new equipment or upgrades to existing equipment.

### A.6.1.4

Since the general definition of ductile refers to a material's ability to be drawn out into a wire, the standard elaborates further by requiring plastic deformation. Another way to relate this concept is by comparison of the material's yield point to its ultimate tensile strength. Materials having non-ductile properties, and that do not deform plastically without fracturing have either a yield point very close to its ultimate tensile strength, or have no yield point value because the yield point is, essentially, equal to its ultimate tensile strength. Acceptable materials will give a clear indication of failure, by first deforming within its plastic range, before ultimate failure actually occurs.

### A.6.1.5

Torque values for threaded connections vary based upon the materials, type of connection, and the predominant forces to which the connection is subjected (e.g. tensile, shear, etc.). Often, a connection will not require a specified torque value, while in some cases a minimum torque value is critical in order to achieve and maintain the full connection strength. Each type of connection and application should be evaluated by a licensed professional engineer in order to determine a) if a minimum torque value is applicable, b) if applicable the actual torque value or range, and c) the correct method for obtaining the specified torque, where required. The use of flat washers is also relevant to minimum torque values. Where no minimum torque values are specified, the use of flat washers is probably not important. Conversely, any time minimum torque values must be achieved, or in applications where slotted or elongated holes are part of the connection, consideration should be given to the use of hardened flat washers as part of the appropriate connection method.

**A.6.2.1.3** A distinction is made between components that are rated based on endurance and specified using service factors, e.g. gear reducers and couplings, and those for which strength is the basis of design such as keys and shafts.

**A.6.3.1** The 33% of yield is approximately equal to the current ASME B30 series requirements for a 5:1 design factor on the static load assuming an additional 75% for dynamic loading.

### A.6.2.4

It is anticipated that the ratio of the drum diameter to that of the wire rope ( $D/d$ ) will have an effect on the static breaking strength of the rope. The  $D/d$  ratio is more likely to have a significant effect on the rate at which the rope fatigues during use and the rate at which the drum or sheave material is eroded by the action of the rope bearing on the groove. Smaller diameter drums tend to increase the stresses in the rope and the "tread pressure" of the rope bearing on the groove. This tends to shorten the life of those components.

References such as the Wire Rope User's Manual<sup>1</sup> may serve as a guide to dimensions such as the radius and depth of the groove that supports the rope. Although valuable as a guide, recommendations within that text are based on specific types of rope constructions or drum materials, and many of the materials in common use within the entertainment industry are not addressed. While making recommendations for  $D/d$  ratios that result in the maximum service life for certain types of wire rope, the

---

1

*Wire Rope User's Manual*. Alexandria, VA: Wire Rope Technical Board

Wire Rope User's Manual acknowledges that those same recommendations are not adhered to in other industrial hoisting standards. Factors such as frequency of use, service life requirements, and the requirements for mechanical efficiency can vary greatly even between different types of machines in the same venue. These factors should be considered when proportions are specified.

The introduction of new types of wire ropes and materials for drums is not uncommon, and it is not the intention of this document to limit their use by imposing restrictions made necessary by those materials most common at the time of writing. In all cases the application of a new material must be consistent with the recommendations of its manufacturer. The manufacturer is often the best source for recommendations concerning design.

#### **A6.2.4.7**

Pile-on drums should be used with caution. As the lifting media winds on to the drum the pitch diameter is increased with each layer, resulting in increased media speed and reduced load capability. The pitch diameter is affected by factors such as the clearance between the lifting media and the drum side plates, and by the crushing, stretching, or distortion of the lifting media. Synchronizing multiple lift lines may be especially difficult.

#### **A.7.1.2**

Dual haul line systems with no additional guide system may be used as a method to restrain rotation of the clew with no additional guide system.

#### **A.8.1**

Users of the system should read and thoroughly understand the information contained in the systems manual. Knowledge of the system-specific load capacities, operating instructions, and maintenance schedules are important to establishing safe operating practices.