



**BSR E1.62 — 201x**

**Minimum specifications for mass-produced portable  
platforms, ramps, stairs, and choral risers for live  
performance events**

Document number: FL/2017-8012r5

Post first public review

Approved by the ANSI Board of Standards Review on \_\_\_\_\_.

## NOTICE AND DISCLAIMER

ESTA does not approve, inspect, or certify any installations, procedures, equipment or materials for compliance with codes, recommended practices or standards. Compliance with a ESTA standard or recommended practice, or an American National Standard developed by ESTA is the sole and exclusive responsibility of the manufacturer or provider and is entirely within their control and discretion. Any markings, identification or other claims of compliance do not constitute certification or approval of any type or nature whatsoever by ESTA.

ESTA neither guarantees nor warrants the accuracy or completeness of any information published herein and disclaim liability for any personal injury, property or other damage or injury of any nature whatsoever, whether special, indirect, consequential or compensatory, directly or indirectly resulting from the publication, use of, or reliance on this document.

In issuing and distributing this document, ESTA does not either (a) undertake to render professional or other services for or on behalf of any person or entity, or (b) undertake any duty to any person or entity with respect to this document or its contents. Anyone using this document should rely on his or her own independent judgment or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstance.

Note: Draft or proposed standards or recommended practices are subject to change. Conformance to a draft or proposed standard or recommended practice is no assurance that the product or service complies with the final approved standard or practice or any other version thereof.

### **Published by:**

The Entertainment Services and Technology Association  
630 Ninth Avenue, Suite 609  
New York, NY 10036  
USA  
Phone: 1-212-244-1505  
Fax: 1-212-244-1502  
standards@esta.org

## **The ESTA Technical Standards Program**

The ESTA Technical Standards Program was created to serve the ESTA membership and the entertainment industry in technical standards related matters. The goal of the Program is to take a leading role regarding technology within the entertainment industry by creating recommended practices and standards, monitoring standards issues around the world on behalf of our members, and improving communications and safety within the industry. ESTA works closely with the technical standards efforts of other organizations within our industry, including ESA, DTHG, USITT, and VPLT, as well as representing the interests of ESTA members to ANSI, UL, and the NFPA. The Technical Standards Program is accredited by the American National Standards Institute.

The Technical Standards Council (TSC) was established to oversee and coordinate the Technical Standards Program. Made up of individuals experienced in standards-making work from throughout our industry, the Council approves all projects undertaken and assigns them to the appropriate working group. The Technical Standards Council employs a Technical Standards Manager to coordinate the work of the Council and its working groups as well as maintain a “Standards Watch” on behalf of members. Working groups include: Control Protocols, Electrical Power, Event Safety, Floors, Fog and Smoke, Followspot Position, Photometrics, Rigging, and Stage Lifts.

ESTA encourages active participation in the Technical Standards Program. There are several ways to become involved. If you would like to become a member of an existing working group, as have over four hundred people, you must complete an application which is available from the ESTA office. Your application is subject to approval by the working group and you will be required to actively participate in the work of the group. This includes responding to letter ballots and attending meetings. Membership in ESTA is not a requirement. You can also become involved by requesting that the TSC develop a standard or a recommended practice in an area of concern to you.

The Floors Working Group, which authored this Standard, consists of a cross section of entertainment industry professionals representing a diversity of interests. ESTA is committed to developing consensus-based standards and recommended practices in an open setting.

**Investors in Innovation**

The Technical Standard Program (TSP) is financially supported by ESTA and by companies and individuals who make undirected donations to the TSP. Contributing companies and individuals who have helped fund the TSP are recognized as “Investors in Innovation.” The Investors in Innovation when this standard was \_\_\_\_\_ include these companies and individuals:

**Update**

All donations to the TSP support the Technical Standards Program in general and are not directed to or for the benefit of any particular technical standard project or any Working Group working on any particular standard or project.

**Contact Information:**

**Technical Standards Manager**

Karl G. Ruling  
The Entertainment Services and Technology Association  
630 Ninth Avenue, Suite 609  
New York, NY 10036  
USA  
1-212-244-1505  
karl.ruling@esta.org

**Assistant Technical Standards Manager**

Erin Grabe  
The Entertainment Services and Technology Association  
630 Ninth Avenue, Suite 609  
New York, NY 10036  
USA  
1-212-244-1505  
erin.grabe@esta.org

**Technical Standards Council Chairpersons**

Mike Garl  
Mike Garl Consulting LLC  
836 Smoke Creek Rd.  
Knoxville, TN 37934  
USA  
1-865-389-4371  
mike@mikegarlconsulting.com

Mike Wood  
Mike Wood Consulting LLC  
6401 Clairmont Drive  
Austin, TX 78749  
USA  
1-512-288-4916  
mike@mikewoodconsulting.com

**Floors Working Group Chairpersons**

Jerry Gorrell  
Theatre Safety Programs  
P. O. Box 17734  
Fountain Hills, AZ 85269  
USA  
1-480-837-9401  
jerryg@jgorrell.com

Tim Hansen  
Oasis Stage Werks  
249 S. Rio Grande Street  
Salt Lake City, UT 84101  
USA  
1-801-363-0364  
thansen@oasis-stage.com

## **Acknowledgments**

The Floors Working Group members when this document was approved by the working group on \_\_\_\_ are shown below.

### **Voting members:**

Fill in

### **Observer (non-voting) members:**

Fill in

### **Interest category codes:**

CP = custom-market producer

DE = designer

DR = dealer rental company

G = general interest

MP = mass-market producer

U = user

## Table of Contents

NOTICE AND DISCLAIMER.....	ii
Investors in Innovation.....	iv
Contact Information.....	v
Acknowledgments.....	vi
1 Scope (mandatory).....	1
2 Rationale for this standard (informative).....	1
3 US/SI conventions (mandatory).....	2
4 Definitions (mandatory).....	2
5 Referenced standards.....	2
6 Construction Requirements (mandatory).....	3
6.1 Fire behavior*.....	3
6.2 Surface finish.....	3
6.3 Requirements for design.....	3
6.3.1 Minimum design loads.....	3
6.3.1.1 Uniformly distributed vertical load*.....	3
6.3.1.2 Vertical point load*.....	3
6.3.1.3 Horizontal loads.....	3
6.3.2 Deflection.....	3
6.3.3 Design calculations and proof testing.....	4
6.3.3.1 Design Calculations.....	4
6.3.3.2 Proof testing*.....	4
6.3.3.2.1 Proof test load.....	4
6.3.3.2.2 Post-test examination.....	4
6.3.3.2.3 Proof test documentation.....	4
7 Additional conditions for access (mandatory).....	4
7.1 Stair units.....	4
7.1.1 Securing.....	4
7.1.2 Vertical point load for stairs*.....	4
7.1.3 Step rise, run, and width*.....	4
7.2 Ramps*.....	4
7.3 Handrails.....	5
8 Fall protection accessories (mandatory).....	5
8.1 General.....	5
8.2 Audience Railings.....	5
8.2.1 Audience Railing design load*.....	5
8.2.2 Audience Railing height and bar spacing*.....	5
8.3 Standard Guardrails*.....	5
8.3.1 Standard Guardrail design load.....	5
8.3.2 Standard Guardrail height and bar spacing.....	5
9 Labeling and user information (mandatory).....	6
9.1 Portable Unit labeling.....	6
9.2 User information.....	6
9.2.1 Operating instructions.....	6
9.2.2 Maintenance instructions.....	6
9.2.3 Warnings and safety notices.....	7
Appendix A Explanatory information (informational, not mandatory).....	8
A.1 (2) Scope.....	8
A.6.1 Fire behavior.....	8
A.6.3.1.1 Uniformly distributed vertical load.....	8
A.6.3.1.2 Vertical point load.....	8

A.6.3.2.2 Proof testing..... 9  
A.7.1.2 Vertical point load for stairs..... 9  
A.7.1.3 Step rise, run, and width..... 9  
A.7.2 Ramps..... 9  
A.8.2.1 Audience Railing design load..... 9  
A.8.2.2 Audience Railing height and bar spacing..... 9  
A.8.3 Standard Guardrails..... 9

Clauses that have an asterisk (\*) have a corresponding informational entry in Appendix A. Appendix A contains no requirements and is informational only.



## 1 Scope (mandatory)

The standard covers mass-produced portable platforms, stair units and ramps used with those platforms, and choral risers, designed to be used for the presentation of music concerts, dramatic plays, fashion shows, and other entertainment and special events. The platforms, stairs, ramps, and choral riser modules covered by this standard are of a size and weight that allows them to be moved and erected by one or two people. Larger, heavier units that require three or more workers to move a module, or that need powered assistance to be moved, are outside the scope of this standard. The scope also covers the railings provided as fall protection accessories for the platforms, stair units, ramps, and choral risers within the scope of this standard.

This standard applies to the legging systems used with the mass-produced portable platforms, stair units and ramps used with those platforms, and choral risers. The legging systems may be integral to the units or separate, but they must be

- (1) designed, manufactured, and sold to be used with the units; or
- (2) supplied by the user or owner of the units in accordance with detailed, specific legging system specifications supplied by the platform manufacturer of the portable platform, stair unit, ramp, or choral riser. \*

Custom platforms; complete stage systems; and platforms, ramps, and stairs used in the construction, maintenance, or repair of buildings are outside the scope of this standard.

## 2 Rationale for this standard (informative)

The products covered by this standard are mass produced and generally sold as equipment to assist in the staging of events. They often are set up for a short period of time in a particular configuration for an event, then are taken down, and stored for use on another event, probably in a different configuration, some time in the future. One or two platforms might be used to support a drummer and trap set for a rock band at a neighborhood bar, or scores of platforms might be used to provide tiered audience seating in a flexible-space, black-box theatre. These products are used and re-used in multiple configurations for a variety of entertainment and special events.

In the United States there are standards for these products when used in particular ways, but not for the products themselves. For example, if the platforms are arranged to provide tiered seating, the complete assembly can be considered a grandstand falling within the scope of NFPA 102, *Standard for Grandstands, Folding and Telescopic Seating, Tents, and Membrane Structures*. However, if they are not used for seating, they are outside the NFPA 102 scope. If platforms are set up as a drum riser for a rock band performing at a bar, the assemblage could be considered a “temporary platform” falling within Section 410 of the *International Building Code*. However, the extremely small size of this structure, the short time that is erected and used, and the venue in which it is being used will make it unlikely that anyone will consider a drum riser as something that should meet the requirements of the *IBC*. In any case, it is not easy to find the *IBC* requirements that might be applied to a drum riser. DIN 15921, *Veranstaltungstechnik – Podeste und Zargen aus Aluminium – Sicherheitstechnische Anforderungen und Prüfung*, applies to aluminum-framed products within the scope of this standard, but the standard is written in German and references EN standards not often used in North America.

The lack of standards that clearly apply to mass-produced, portable platforms complicates the US market for them. Manufacturers will sometimes contact ESTA's office to ask with what standards they will need to comply, and that results in an overly long conversation. Stage technicians and venue managers who use these platforms are sometimes asked by a supervisor what product standards the platforms meet, and the unsatisfactory answer is, “Well, it depends on how we use them.”

While there are no standards in North America for these portable platforms as products, there is significant congruence for the minimum performance specifications among the various standards and codes that can

be applied to them when used in various ways. This standard attempts to incorporate those performance requirements into a product standard.

### 3 US/SI conventions (mandatory)

This Standard uses both United States customary units and the International System of Units in parenthesis for stating its requirements. The requirement statements are not exactly equivalent between US customary units and SI, but the difference is insignificant for the purposes of this Standard. A requirement shall be considered to be met if a product meets the requirement whether expressed in US customary units or SI.

### 4 Definitions (mandatory)

**Audience Railing:** A handrail or railing for fall protection in areas accessible to the general public.

**Payload:** The load that can be supported by a Portable Unit in addition to its own weight.

**Portable Unit:** A platform, stair unit, ramp, or choral riser that is within the scope of this standard.

**Qualified Person:** A person who by possession of a recognized degree or certificate of professional standing, or who by extensive knowledge, training, and experience, has successfully demonstrated the ability to solve or resolve problems relating to the subject matter and work.

**Shall:** Indicates a mandatory requirement.

**Should:** Indicates a recommendation that is not a mandatory requirement.

**Standard Guardrail:** A railing for fall protection in areas not accessible to the general public.

### 5 Referenced standards

The following standards were referenced in the writing of this Standard. This Standard in general does not require compliance with these standards, except where specifically stated in a requirement of this Standard. However, the user of this standard is encouraged to consult these listed standards to gain an understanding of the context in which this Standard has been developed.

Note that compliance with these standards may be mandatory due to regulations or contractual obligations that might apply to users of this standard. That is, the lack of a compliance requirement in this Standard does not obviate the need to comply with a referenced standard if that compliance is required by a regulation.

- 29 CFR 1910.25, Stairways
- 29 CFR 1910.29, Fall protection systems and falling object protection-criteria and practices.
- 2010 ADA Standards for Accessible Design.
- 2015 Aluminum Design Manual
- 2018 International Building Code® (referred to in this Standard as “the 2018 IBC”)
- ANSI Z535.4 - 2011 (R2017), Product Safety Signs and Labels
- ANSI Z535.6 - 2011 (R2017), Product Safety Information in Product Manuals, Instructions, and Other Collateral Materials
- ASTM E84-18, Standard Test Method for Surface Burning Characteristics of Building Materials.
- DIN 15921:2015, Veranstaltungstechnik – Podeste und Zargen aus Aluminium – Sicherheitstechnische Anforderungen und Prüfung
- ICC 300-2012, Standard for Bleachers, Folding and Telescopic Seating, and Grandstands
- National Design Specification for Wood Construction, 2018 edition

- NFPA 102, Standard for Grandstands, Folding and Telescopic Seating, Tents, and Membrane Structures, 2016 edition
- NFPA 5000, Building Construction and Safety Code, 2018 edition (NFPA 5000-2018)
- Steel Construction Manual, 13th Edition
- UL 723, Standard for Test for Surface Burning Characteristics of Building Materials, 2008 edition

## **6 Construction Requirements (mandatory)**

### **6.1 Fire behavior\***

The material used to construct Portable Units shall have flame spread and smoke-developed indices equal to or less than Class B as defined by UL 723, Standard for Test for Surface Burning Characteristics of Building Materials, or as defined by ASTM E84, Standard Test Method for Surface Burning Characteristics of Building Materials.

### **6.2 Surface finish**

To avoid injury to persons, accessible edges, corners, and protruding parts must be burr-free. The grip areas for manual handling of the Portable Units should be designed according to ergonomic principles. As an alternative, the construction may allow for the use of accessories, such as ergonomically shaped carrying handles, to allow the safe manual handling platforms, stair units, ramps, and choral risers.

Corrosion-prone parts of metal must be protected by paint or other coatings.

The walking surfaces of Portable Units shall be free from splinters, trip-hazards, and sharp edges.

### **6.3 Requirements for design**

#### **6.3.1 Minimum design loads**

##### **6.3.1.1 Uniformly distributed vertical load\***

Walking surfaces of Portable Units shall be designed to be able to support an evenly distributed vertical load of at least 100 pounds/square foot (4.8 kN/m<sup>2</sup>).

##### **6.3.1.2 Vertical point load\***

With the exception of stair units, walking surfaces of Portable Units shall be designed to be able to support a minimum point load of 300 pounds anywhere on the walking surface on an area 2 inches by 2 inches (1.3 kN on an area 51 mm X 51 mm). The point load shall not be required to be supported at the same time as the uniformly distributed load.

##### **6.3.1.3 Horizontal loads**

Portable Units shall support a horizontally directed load applied at the level of the upper walking surface with a force equal to 1/10 of the payload specified according to 6.3.1.1 or 1/10 the payload claimed for the Portable Unit by the manufacturer, whichever is greater.

#### **6.3.2 Deflection**

In order to avoid creating a trip hazard, the difference in height between the surfaces of adjacent Portable Units sitting on a planar surface must not be more than 5/64" (2 mm) in an unloaded condition and not more than 5/32" (4 mm) with the maximum permissible load on one unit and no load on the adjacent one. This is to be assured by limiting the deflection under load or by providing a means of attaching platforms together or by a combination of both methods.

This maximum deflection under load shall be determined and reported in the documentation available to the specifier or user of the Portable Unit.

### **6.3.3 Design calculations and proof testing**

#### **6.3.3.1 Design Calculations**

**6.3.3.1.1** Design shall be performed in accordance with established engineering practice by a Qualified Person.

**6.3.3.1.2** Portable Units shall be designed to support the loads specified in this Standard.

**6.3.3.1.3** The strength of Portable Units shall be established using either Load and Resistance Factor Design or Allowable Stress Design methods, or by proof testing.

#### **6.3.3.2 Proof testing\***

Proof testing shall be carried out when Load and Resistance Factor Design or Allowable Stress Design can not be done for any reason or when verification of the design is desirable or required.

##### **6.3.3.2.1 Proof test load**

The proof test load shall be 1.5 times the design load if the major structural members of the Portable Unit are steel, 1.65 the design load if the major structural members of the Portable Unit are aluminum, and 2.0 if the major structural members of the Portable Unit are of any other material, for example, wood.

##### **6.3.3.2.2 Post-test examination**

After the proof test, the tested Portable Unit shall be examined to determine if the testing procedure broke, cracked, or permanently deformed any part of the Portable Unit. This examination may require that the Portable Unit be disassembled.

##### **6.3.3.2.3 Proof test documentation**

The proof testing procedure shall be documented in enough detail that the test can be duplicated by any party. The documentation shall be preserved on file for the expected life of the product, plus five years.

## **7 Additional conditions for access (mandatory)**

### **7.1 Stair units**

#### **7.1.1 Securing**

Stair units shall be fitted with devices to ensure that they don't shift away from any platform to which they provide access during use.

#### **7.1.2 Vertical point load for stairs\***

Stair units shall be able to support a minimum point load of 1000 pounds anywhere on the walking surface on an area 2 inches by 2 inches (4.4 kN on an area 51 mm X 51 mm).

#### **7.1.3 Step rise, run, and width\***

The maximum riser height shall be 9.5 inches (24 cm). The minimum tread depth shall be 9.5 inches (24 cm). The minimum tread width shall be 22 inches (56 cm).

Multi-step units shall have a uniform tread depth and rise, varying less than 0.19 inches (5 mm) from step to step.

### **7.2 Ramps\***

Ramps must be able to support the minimum design loads specified in 6.3.1 and should have the same load-bearing ability as the platform surfaces to which they are designed to lead. A slope of 1:8 (12.5%) must not be exceeded. A maximum inclination of 1:16.6 (6%) should not be exceeded for barrier-free access (e.g. for wheelchairs). The minimum width should be 36 inches (91 cm) for wheelchair access.

### **7.3 Handrails**

Stair units and ramps having a rise of 8 inches (20 cm) or more shall have a provision for mounting at least one handrail. Multi-step stair units and ramps wider than 47 inches (1.2 meters) shall have a provision for mounting two handrails.

Handrails will need to meet the requirements for a Standard Guardrail at a minimum, and may need to meet the requirements for Audience Railings when the stair units are in public areas and there is a fall hazard. The handrail mounting must be designed to support either type of railing.

## **8 Fall protection accessories (mandatory)**

### **8.1 General**

Fall protection is generally provided by Audience Railings or Standard Guardrails. Other fall protection, such as nets and personal fall arrest systems, or work positioning systems to make falls impossible, could be used, but their use would be rare and these devices are outside the scope of this Standard.

For the purposes of this Standard, it should be assumed that any portable platform, stair unit, ramp, or choral riser that has or can have a walking or standing surface 8 inches (20 cm) or more above the supporting floor should have a means to attach Audience Railings or Standard Guardrails.

### **8.2 Audience Railings**

#### **8.2.1 Audience Railing design load\***

Audience Railings shall be designed to support a concentrated load of at least 200 pounds (0.9 kN) applied in any direction on the top rail. They shall be able to support a uniformly distributed load of 50 pounds per linear foot of railing length (0.73 kN/m).

Intermediate rails (all those except the top rail) shall be designed to withstand a horizontal load of 50 pounds (0.22 kN) applied to an area of one foot square (30.5 cm x 30.5 cm). The application of the load shall not cause the intermediate structure to bend or tear to create an opening larger than allowed in 8.2.2.

#### **8.2.2 Audience Railing height and bar spacing\***

Audience Railings shall have a height of at least 42 inches (1.1 m). The bottom of the railing structure shall be designed to not be more than 0.8 inches (20 mm) above Portable Unit to which it would be fastened. The space between the top and bottom of the Audience Railing shall be filled with intermediate rails or a structure of bars, panels, or other elements spaced so that a 4-inch (100 mm) ball cannot be pushed through the structure.

### **8.3 Standard Guardrails\***

#### **8.3.1 Standard Guardrail design load**

Standard Guardrails shall be designed to support a concentrated load of at least 200 pounds (0.9 kN) applied in any direction on the top rail. They shall be able to support a uniformly distributed load of 50 pounds per linear foot of railing length (0.73 kN/m).

Intermediate rails, bars, or panels shall be designed to withstand without failure a force of at least 150 pounds (0.7 kN) applied in any downward or outward direction at any point along the intermediate member.

#### **8.3.2 Standard Guardrail height and bar spacing**

Standard Guardrails shall have a height of at least 42 inches (1.1 m). The bottom of the railing structure shall be designed to not be more than 0.8 inches (20 mm) above Portable Unit to which it would be fastened. The space between the top and bottom of the Standard Guardrail shall be filled with

intermediate rails or a structure of bars, panels, or other elements so there is no space larger than 19 inches (48 cm).

## **9 Labeling and user information (mandatory)**

### **9.1 Portable Unit labeling**

The Portable Unit shall have a durable label on it that specifies:

- 1) manufacturer with contact name;
- 2) manufacture year and month;
- 3) product name;
- 4) self-weight in kilograms or pounds;
- 5) the permissible payload as a function of the maximum permissible height, and the permissible leg positions;
- 6) the maximum permissible point loads;
- 7) the maximum vertical or horizontal deflection under load
- 8) the fire behavior classification (see clause 6.1)

### **9.2 User information**

The following information should be provided to the user on the Portable Unit, in a hard-copy handbook, on a website, in a free app for portable devices, or via some other convenient medium.

#### **9.2.1 Operating instructions**

The manufacturer, importer or distributor must provide a user manual with the user information.

- a) description of the installation and use situation (e.g., fitness for outdoor use);
- b) the correct assembly of the Portable Unit;
- c) instructions for the correct positioning of the protective electrical bonding connection, if one exists;
- d) recommendations for preventive measures to be taken by the user (e.g., personal protective gear);
- e) instructions for assembly, dismantling, and operation, and the number of people required for manual handling indicated;
- f) information on the static load capacity and on variable or mobile loads (e.g., vehicles, wheelchairs);
- g) information on storage and transport;
- h) notes on maintenance (repair, maintenance, testing)
- i) criteria for decommissioning and disposal;
- j) information on spare parts procurement.

#### **9.2.2 Maintenance instructions**

Maintenance instructions should include the following:

- a) advice about the nature and frequency of visual and functional checks, inspections, and maintenance;
- b) particular hazards during inspections and maintenance;

- c) qualification of the persons responsible for the inspection and maintenance;
- d) instructions for repairs and adjustments;
- e) cleaning and care methods;
- f) the scope of inspections and maintenance that may be carried out without the involvement of specialists;
- g) contact details of the manufacturer of the Portable Unit from which technical support is available.

### **9.2.3 Warnings and safety notices**

Hazards shall be identified and reported to the user by appropriate labeling and safety notices per ANSI Z535.4 - 2011 (R2017), Product Safety Signs and Labels and ANSI Z535.6 - 2011 (R2017), Product Safety Information in Product Manuals, Instructions, and Other Collateral Materials.

## **Appendix A**

### **Explanatory information**

#### **(informational, not mandatory)**

### **A.1 (2) Scope**

A few platform systems are manufactured with sockets in the corners for user-supplied legs. The legs often are specified as needing to be of a particular type of pipe or tubing. Often the portable platform manufacturer will publish load performance specifications with the understanding that user will supply legs per the platform manufacturers instructions. The instructions should be detailed and specific, or the user-supplied legs will be an undefined element, and no meaningful statements can be made about the platform load-carrying capacity.

### **A.6.1 Fire behavior**

The fire behavior specification is taken from clause 803.1.2, Interior wall and ceiling finish materials, of the 2018 International Building Code. That clause is about limiting flame and smoke spread, which, for the purposes of this standard, are considered the major fire hazards with portable platforms, not their contribution to the potential fuel load of a building. The frames of most mass-produced portable platforms, stair units, ramps, and choral risers are made of aluminum or steel, which are usually considered non-combustible, but the walking surfaces (decks) are often made of wood, plastic, or some combination of the two. In some situations, these might burn, but it is desirable to limit the rate of flame spread and smoke production.

DIN 15921 only addresses the flammability of the deck material and requires that it must at a minimum be out of normally inflammable materials. (“. . . müssen mindestens aus normalentflammbaren Materialien bestehen.”) It does not require that the decks not burn, but that they burn no more readily than normal. However, for a North American audience, arguments about what constitutes “normal burning” are likely to be unsatisfying.

NFPA 102 cites sections of NFPA 5000 for grandstand construction requirements. Different maximum heights, maximum areas, and minimum distances from buildings are specified, depending on the construction type (i.e., Type I, Type II, Type III, Type IV, or Type V). That classification system does not work well for small, modular, portable units.

#### **A.6.3.1.1 Uniformly distributed vertical load**

The 2018 International Building Code specifies a minimum UDL for “Platforms (assembly),” “Other assembly areas,” and “Reviewing stands, grandstands and bleachers” in Table 1607.1 of 100 pounds per square foot. DIN 15921 specifies 5 kN/m<sup>2</sup>, which is about 104 pounds per square foot. This is a higher specification, but not so much as to suggest that the IBC is wrong.

NFPAS 102 cites clauses in NFPA 5000 which cite clauses in ASCE 7. The 2005 edition of ASCE 7 specifies the same minimum loading as the 2018 IBC.

#### **A.6.3.1.2 Vertical point load**

This point load specification is taken from ICC 300. DIN 15921 specifies a higher minimum vertical point load of 1.5 kN on a square footprint 50 mm x 50 mm. (“Es ist eine vertikale Last von mindestens 1,5 kN mit einer quadratischen Aufstandsfläche mit einer Seitenlänge von 50 mm in ungünstigster Stellung anzusetzen.”) That is about 337 pounds-force on a square 1.97” on a side.



### **A.6.3.2.2 Proof testing**

See Annex A of DIN 15921:2015, Veranstaltungstechnik – Podeste und Zargen aus Aluminium – Sicherheitstechnische Anforderungen und Prüfung, for proof testing jigs and procedures. The text is in German, but it is not particularly difficult German, and the illustrations are easy to understand.

### **A.7.1.2 Vertical point load for stairs**

This specification is taken from 29 CFR 1910.25(b)(6). It is more severe than the specification in DIN 15921:2015, clause 4.3.1, which requires stairways to withstand a point load of 1.5 kN (337 pounds) on a surface of 100 mm × 100 mm.

### **A.7.1.3 Step rise, run, and width**

These rise, run, and width minimum specifications are taken from 29 CFR 1910.25(c)(2), 1910.25(c)(3), and 1910.25(c)(4). These OSHA regulations allow a higher rise and shorter tread depth than are allowed for assembly occupancy aisle stairs in NFPA 5000-2018.

The uniformity specification is based on ICC 300-2012, which defines nonuniformity as a variation of 0.188 inches (4.8 mm) or more. This Standard rounds the US customary unit specification to two significant digits and applies a similar rounding to the SI equivalent. A piece of 20-pound paper is about 0.00325 inches thick; taking the specification for step uniformity to a level of precision thinner than a piece of paper, as ICC 300 does, is unlikely to be helpful.

### **A.7.2 Ramps**

The slope specification is copied from a translation of DIN 15921:2015, but the 1:8 (12.5%) maximum is consistent with clause 16.2.5.6.5.1 (2) in NFPA 5000-2018. Per that clause, any assembly occupancy aisle steeper than 1:8 is required to be a stairway. The 1:16 slope for wheelchair access is lower than the 1:12 stated in clause 405.2 in the Department of Justice's *2010 ADA Standards for Accessible Design*. However, that document also says, "Where possible, designers and operators are encouraged to provide ramps with a slope less than the 1:12 maximum." (Advisory 240.2.1).

### **A.8.2.1 Audience Railing design load**

These specifications are taken from ICC 300-2012. They are lower than what is required in DIN 15921:2015. That standard requires the design load at a 1m rail height to be 1 kN/m (69 pounds/foot), but at least 1 kN (225 pounds-force) in the direction of a possible fall, and 0.5 kN/m (34 pounds/foot), but at least 0.5 kN, in the direction away from the fall hazard, back toward the platform center.

### **A.8.2.2 Audience Railing height and bar spacing**

These height and spacing requirements are broadly consistent across DIN 15921:2015, ICC 300-2012, and NFPA 102-2016. The DIN standard is more specific about the structure that fills the space between the top and bottom of the railing, requiring it to be made of vertical bars, but it also allows a wider spacing, 120 mm. The purpose of requiring vertical bars is to make climbing over the railing difficult.

### **A.8.3 Standard Guardrails**

These requirements are essentially those found in 29 CFR 1910.29(b) with the addition of a uniformly distributed load requirement.