



ANSI E1.40 - 2016
Recommendations for the Planning of
Theatrical Dust Effects

F&S/2010-3003r3

Copyright 2016 the Entertainment Services and Technology Association
All rights reserved.

Approved as an American National Standard by the ANSI Board of Standards Review on
16 September 2016.

NOTICE and DISCLAIMER

ESTA does not approve, inspect, or certify any installations, procedures, equipment or materials for compliance with codes, recommended practices or standards. Compliance with a ESTA standard or an American National Standard developed by ESTA is the sole and exclusive responsibility of the manufacturer or provider and is entirely within their control and discretion. Any markings, identification or other claims of compliance do not constitute certification or approval of any type or nature whatsoever by ESTA.

ESTA neither guarantees nor warrants the accuracy or completeness of any information published herein and disclaims liability for any personal injury, property or other damage or injury of any nature whatsoever, whether special, indirect, consequential or compensatory, directly or indirectly resulting from the publication, use of, or reliance on this document. In issuing and distributing this document.

In issuing this document, ESTA does not either (a) undertake to render professional or other services for or on behalf of any person or entity, or (b) undertake any duty to any person or entity with respect to this document or its contents. Anyone using this document should rely on his or her own independent judgment or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstance.

Published by:

The Entertainment Services and Technology Association
630 Ninth Avenue, Suite 609
New York, NY 10036
USA
Phone: 1-212-244-1505
Fax: 1-212-244-1502
Email: standards@esta.org

The ESTA Technical Standards Program

The ESTA Technical Standards Program was created to serve the ESTA membership and the entertainment industry in technical standards related matters. The goal of the Program is to take a leading role regarding technology within the entertainment industry by creating recommended practices and standards, monitoring standards issues around the world on behalf of our members, and improving communications and safety within the industry. ESTA works closely with the technical standards efforts of other organizations within our industry, including USITT and VPLT, as well as representing the interests of ESTA members to ANSI, UL, and the NFPA. The Technical Standards Program is accredited by the American National Standards Institute.

The Technical Standards Council (TSC) was established to oversee and coordinate the Technical Standards Program. Made up of individuals experienced in standards-making work from throughout our industry, the Council approves all projects undertaken and assigns them to the appropriate working group. The Technical Standards Council employs a Technical Standards Manager to coordinate the work of the Council and its working groups as well as maintain a "Standards Watch" on behalf of members. Working groups include: Control Protocols, Electrical Power, Floors, Fog and Smoke, Followspot Position, Photometrics, Rigging, and Stage Lifts.

ESTA encourages active participation in the Technical Standards Program. There are several ways to become involved. If you would like to become a member of an existing working group, as have over four hundred people, you must complete an application which is available from the ESTA office. Your application is subject to approval by the working group and you will be required to actively participate in the work of the group. This includes responding to letter ballots and attending meetings. Membership in ESTA is not a requirement. You can also become involved by requesting that the TSC develop a standard or a recommended practice in an area of concern to you.

The Fog & Smoke Working Group, which authored this Standard, consists of a cross section of entertainment industry professionals representing a diversity of interests. ESTA is committed to developing consensus-based standards and recommended practices in an open setting.

Investors in Innovation

The Technical Standard Program (TSP) is financially supported by ESTA and by companies and individuals who make undirected donations to the TSP. Contributing companies and individuals who have helped fund the TSP are recognized as “Investors in Innovation”. The Investors in Innovation when this standard was approved by the working group include these companies and individuals:

<p>VISIONARY (\$10,000 & up; >100 employees/members) Columbus McKinnon ETC LDI</p>	<p>ProSight Specialty Insurance United States Institute for Theatre Technology</p>
<p>VISIONARY (\$5,000 & up; 20–100 employees/members) Altman Lighting, Inc.</p>	<p>JR Clancy</p>
<p>VISIONARY (\$500 & up; <20 employees/members) B-Hive Industries, Inc. Boston Illumination group Candela Controls Inc. EGI Event Production Services* John T. McGraw Sapsis Rigging Inc.</p>	<p>Steve Terry Theatre Projects Theatre Safety Programs Steve A. Walker & Associates* Ralph Weber</p>
<p>INVESTOR (\$3,000–\$9,999; >100 employees/members) Barbizon Electric Lex</p>	<p>Rosco Laboratories Texas Scenic Company</p>
<p>INVESTOR (\$1,500–\$4,999; 20–100 employees/members) American Society of Theatre Consultants</p>	<p>H&H Specialties, Inc.</p>
<p>INVESTOR (\$200–\$499; <20 employees/members) Indianapolis Stage Sales & Rentals, Inc.* LuciTag Lumenradio AB</p>	<p>Nudelta Digital Project SSSH Incorporated</p>
<p>SUPPORTER (<\$3,000; >100 employees/members) Ian Foulds, IATSE Local 873 IATSE Local 80</p>	<p>PSAV</p>
<p>SUPPORTER (<\$1,500; 20–100 employees/members) Blizzard Lighting, LLC Lycian Stage Lighting Oasis Stage Werks Stage Equipment & Lighting</p>	<p>TOMCAT Total Structures* Vincent Lighting Systems*</p>
<p>SUPPORTER (<\$200; <20 employees/members) Milton Davis Michael Lay Niscon Inc. Skjonberg Controls Inc. *Investor for over 15 years</p>	<p>Christopher B. Tilton Tracy Underhill Ken Vannice</p>

All donations to the TSP support the Technical Standards Program in general and are not directed to or for the benefit of any particular technical standard project or any Working Group working on any particular standard or project. If you would like to help support the Technical Standards Program in its work, please consider becoming an Investor in Innovation by visiting our website at <http://tsp.esta.org/invest> or contacting standards@esta.org.

Downloaded from TSP.ESTA.ORG. Dowload sponsored by Prosight Specialty Insurance.

Contact Information

Technical Standards Manager

Karl G. Ruling
The Entertainment Services and Technology Association
630 Ninth Avenue, Suite 609
New York, NY 10036
USA
1-212-244-1505 x.703
karl.ruling@esta.org

Assistant Technical Standards Manager

Erin Grabe
The Entertainment Services and Technology Association
630 Ninth Avenue, Suite 609
New York, NY 10036
USA
1-212-244-1505 x.606
erin.grabe@esta.org

Technical Standards Council Chairpersons

Mike Garl
Mike Garl Consulting LLC
1-865-389-4371
mike@mikegarlconsulting.com

Mike Wood
Mike Wood Consulting LLC
1-512-288-4916
mike@mikewoodconsulting.com

Fog & Smoke Working Group Co-chairpersons

M. Brad Dittmer
Stage Labor of the Ozarks
+1-417-616-9948
slobrad@gmail.com

Larry Schoeneman
Designlab Chicago, Inc.
+1-773-265-1100 x.13
larry@dlabchicago.net

Acknowledgments

The Fog & Smoke Working Group members when this document was approved by the working group on 25 July 2016 are shown below.

Voting members:

Matthew Antonucci - Contract Services Administration Trust Fund (U)
Brad Dittmer - Stage Labor of the Ozarks (U)
Mark Elliott - Walt Disney Company (U)
Paul Jordan - NBC Universal (U)
Edwin S. Kramer - I.A.T.S.E. Local 1 (DE)
Karl G. Ruling - Unit 12 Productions (CP)
Marnie Styles - Ultratec Special Effects Inc. (MP)
Steve Vanciel - IATSE Local 631 (U)
Mike Wood - Mike Wood Consulting LLC (G)

Observer (non-voting) members:

Robert Barbagallo - Solotech Inc.
Paul Beasley - Walt Disney Company
Margaret Buckalew - Environmental Resource Management (ERM)
Justin Cicerone - Harman International Industries
Gary Crawford - C I T C
Jerry Gorrell - Theatre Safety Programs
Kent H. Jorgensen - IATSE Local 80
Nathan Kahn - Look Solutions USA Ltd.
Martin Michaud - MDG Fog Generators Ltd.
Monona Rossol - Monona Rossol
Larry Schoeneman - DesignLab Chicago, Inc.
Ford Sellers - Chauvet Lighting
Colin Waters - TMB

Interest category codes:

CP = custom-market producer	DE = designer
DR = dealer rental company	G = general interest
MP = mass-market producer	U = user

Table of Contents

The ESTA Technical Standards Program.....	2
Investors in Innovation.....	3
Contact Information.....	4
Acknowledgments.....	5
Table of Contents.....	6
Basic Dust Use Guidelines.....	1
1 Scope	2
2 Introduction.....	2
3 Major Categories of Dust.....	2
3.1 Plant and animal-based.....	2
3.2 Mineral.....	2
3.3 Synthetic.....	2
4 Potential Hazards of Dust.....	3
4.1 Exposure.....	3
4.1.1 Topical Exposure and Allergies.....	3
4.1.2 Inhalation.....	3
4.2 Combustion.....	4
5 Risk Reduction.....	5
5.1 Product Selection.....	5
5.2 Product Usage.....	5
5.3 Use PPE and Appropriate Tools.....	6

Basic Dust Use Guidelines

- Determine the appropriate product for the application.
- Ensure you know the precise composition of the product you are using.
- Obtain an Safety Data Sheet (previously called a Material Safety Data Sheet, or MSDS) for the product and abide by any associated exposure limits.
- Use only as much dust as necessary.
- Use dust only where it is necessary.
- Use dust only when it is necessary.
- Avoid exposing unnecessary personnel.
- Monitor and control usage and ventilation throughout.
- Inform personnel on the products being used and post appropriate warnings.
- Follow manufacturers' instructions.
- Use appropriate Personal Protective Equipment (PPE).
- Use appropriate equipment and tools.
- Read this document and follow the recommendations listed.

1 Scope

A wide variety of products are used to create dust effects in entertainment productions. Such effects are most commonly used in motion picture and television production; However, they are also used in theatrical productions and within theme parks. The use of dust in this manner raises concerns for potential hazards including combustibility and health effects from inhalation or ingestion, which, although well known in some sectors of the industry, are poorly understood in others. This document provides recommendations for how to plan the use and assess the safety of such effects.

2 Introduction

The word *dust* is non-specific and means different things to different people. Dust is used in this document as a generic term referring to any solid particles scattered or suspended in the air where the common denominator is the use to which it is put, as a set dressing or as a special effect. Dust can be used in small quantities, such as to sprinkle on books or props to age them or to enhance artificial cobwebs, all the way up to extensive use on film sets where a complete realistic environment is being created. Dust use in film sets for special effects is very common, and the users in that industry are usually more familiar with the techniques than those in theatrical venues. However, the same basic principles of safe operation apply to everyone, no matter the application.

3 Major Categories of Dust

The dust used in theatrical effects generally can be broken down into three major categories—plant and animal-based, mineral, and synthetic—depending on the source of the dust.

3.1 Plant and animal-based

Plant and animal-based dusts are those based on naturally occurring products from plants or animals. Examples of common products derived from plants or animals that have been used as a theatrical dust effect include wheat flour, rice flour, rice gluten, corn starch, coffee creamers, and crushed nutshells.

3.2 Mineral

Mineral-based dusts include fuller's earth, kaolin, aluminum magnesium silicate, pyrolite, pyrophyllite, and diatomaceous earth. Diatomaceous earth is the fossilized remains of diatoms and hard-shelled algae, so it could be classified as a plant or animal-based dust, but fossilization leaves only the mineral remains of those life-forms, particularly silica, behind in the diatomaceous earth.

3.3 Synthetic

There are many synthetic products that might be used to make dust. Colored dyes, ground plastics, and extremely high density glycols, such as polyethylene glycol 3350, might be among the things considered for dust effects.

Note: None of these classifications (plant and animal-based, mineral, or synthetic) is inherently safer than another. For example, wood dust is a plant product, but most wood dusts are confirmed carcinogens. Titanium dioxide is a white pigment that is found in minerals such as rutile and anatase. (Rutile is about 98% titanium dioxide.) The International Agency for Research on Cancer has classified it as a group 2B carcinogen based on inhalation studies.

4 Potential Hazards of Dust

4.1 Exposure

4.1.1 Topical Exposure and Allergies

In low concentrations dust can cause immediate topical irritation of the eyes, skin, nose, and throat. These irritations can be exacerbated if the exposed person is allergic or sensitive to the specific material, particularly if it is an organic dust. Irritation may be caused either by mechanical or chemical irritant characteristics of the dust. For applicable products, the SDS should list the potential mode(s) of irritation.

4.1.2 Inhalation

Dust may also be inhaled into the lungs. The lungs are protected by a series of defense mechanisms in different regions of the respiratory tract. When a person breathes in the nose and upper throat efficiently filter out most large particles, until they are removed mechanically by blowing the nose, sneezing, or coughing.

Some smaller particles will succeed in passing through the nose to reach the windpipe and the dividing air tubes that lead to the lungs. These airways are lined by cells that produce mucus that catches most of the remaining dust particles. Tiny hairs called cilia, covering the walls of the air tubes, move the mucus upward and out into the throat, where it is either coughed up and spat out, or swallowed.

If the dust particles are small enough they may avoid these defenses and reach the tiny air sacs (alveoli) in the deeper parts of the lungs. Depending on the particles degradability and solubility in body fluids or in cells, the particles may dissolve and enter the blood stream, may be broken down and the byproducts metabolized, or they remain in the alveoli indefinitely.

Generally, dust can cause respiratory health effects in two ways: by being trapped in the lungs where it can cause local damage or irritation, or by absorption directly into the bloodstream. Ingestion of toxic dust can also cause adverse health effects by absorption through the digestive system.

4.1.2.1 Silica

Of particular concern for deep lung inhalation are inorganic dusts containing crystalline silicon dioxide, also known as silica. The term "silica" is often used commonly to refer to at least three substances that contain silicon, but only the first of these contains forms of crystalline silica.

- crystalline silica, such as sand or quartz.
- amorphous silica (non-crystalline)
- silicates, such as clay (aluminum silicates)

It is only the crystalline form (free silica) found in quartz, tridymite, cristobalite, and other nonsilicates that cause silicosis. Silicosis is a slow cumulative lung disease caused by the inhalation of free silica particulates, which may not manifest itself until many years after exposure. The mechanism is as follows: after the macrophages ingest silica particles, they die and give off toxic substances. These substances cause localized fibrous or scar tissue to form in the lungs. This tissue is the body's normal way of repairing itself, however, in the case of crystalline silica so much fibrous tissue and scarring can form that lung function may be impaired. The general name for this condition of fibrous tissue formation and scarring is fibrosis, and the particles that cause fibrosis or scarring are called fibrogenic. When fibrosis is caused by crystalline silica, the condition is called silicosis. Silica in the crystalline form also is a confirmed carcinogen.

Amorphous silica and the many various silicates do not cause silicosis. However, they have been associated with respiratory irritation and other adverse effects. There are air quality standards for some of

Downloaded from TSP.ETA.ORG. Download sponsored by ProSight Specialty Insurance.

the silicate minerals, but there is not enough data on most of them to set standards. These dust should not be considered to be without hazards. Those silicates that can reach the alveoli are likely to remain for life. Most silicates also are found in nature contaminated with some crystalline silica.

4.1.2.2 Fuller's Earth

Historically fuller's earth was commonly used for theatrical dust. However, fuller's earth is an inadequate catch-all name with no agreed or defined composition and is often used as a generic term to describe a broad range of kaolin (clay) based products containing aluminum magnesium silicate. Fuller's earth may also be known as montmorillonite, kaolin, kaolinite, floridin, bentonite, wilkonite, and halloysite.

Fuller's earth is no longer widely used as a theatrical dust product because of the product's historically high free silica content. If you intend to use fuller's earth it is important to obtain a current Safety Data Sheet (SDS) for the specific product you are using and to check the crystalline silica content of that specific product. Although a product is not called fuller's earth, it does not mean it is free of crystalline silica.

4.1.2.3 Wood

The dust from many forms of wood are now thought to be carcinogenic by the American Conference of Governmental Industrial Hygienists (ACGIH). Currently, OSHA regulates wood dust as a nuisance dust. However, OSHA encourages employers to keep exposures to a minimum and to observe the ACGIH Threshold Limit Value (TLV) levels.

4.2 Combustion

Finely dividing a material into a dust vastly increases the surface area of the product in contact with air and can turn a material that is only slightly combustible into a severe fire or explosion hazard. This is a particular problem with plant and animal-based dusts; common materials such as flour can be highly explosive when finely dispersed in the air. OSHA 3371-08 2009 - Health Communication Guidance on Combustible Dusts contains generic advice on dealing with and mitigating such hazards and lists the following materials as examples of potential explosion hazards: metal dust, such as aluminum and magnesium; wood dust; plastic or rubber dust; biosolids; coal dust; plant and animal-based dusts, such as flour, sugar, paper, soap, and dried blood; and dusts from certain textiles.

Different dusts of the same chemical material can have different ignitability and explosibility characteristics, depending upon physical characteristics such as particle size, shape, and moisture content. These physical characteristics can change during manufacturing, use or while the material is being processed.

There are five key elements for a dust fire or explosion; if these elements are missing a fire or explosion cannot occur. The first three elements are those needed for any fire, i.e., the familiar fire triangle:

1. Combustible dust (fuel)
2. Ignition source (heat)
3. Oxygen in air (oxidizer)

An additional element must be present for a combustible dust flash-fire, technically called a deflagration:

4. Dispersion of dust particles in the air in sufficient quantity and concentration

The resulting deflagration can be exacerbated by confinement to make a combustible dust explosion:

5. Confinement of the dust cloud.

Downloaded from TSP.ETA.ORG. Dowload sponsored by Prosgit Specialty Insurance.

If the use of a potentially combustible dust is contemplated, mitigation of these five elements must be considered. Of these, the most important is insuring the dust is not dispersed in the air in significant amounts. Even removing all ignition sources including heat, sparks, and flame, cannot ensure that the dust will not be ignited by an unexpected static discharge. Clean up of these substances also must be done without creating airborne dust clouds.

A combustible dust cloud in a room or confined area is more dangerous than one out in the open. However, a cloud of dust can ignite and burn in the open causing harm to those in or near the cloud.

5 Risk Reduction

5.1 Product Selection

- First and foremost make sure you know the precise composition of the product you are using.
- Obtain and read a Safety Data Sheet for the product and abide by any associated exposure limits. Many products have Permissible Exposure Limits (PEL) established by Federal or State OSHA. Refer to Federal and State OSHA Regulations for further information.
- Give preference to materials for which there are recognized exposure limits and avoid using materials for which there are no recognized limits.
- If non-organic materials are used, pay particular attention to the crystalline or free silica content.
- Avoid using products containing known carcinogens.
- Consult the SDS to identify if a material or product contains a sensitizer and avoid using products containing known sensitizers.
- Use the largest particle size commensurate with achieving the desired effect. In particular, products containing a significant concentration of particles under 10 microns, which are more likely to be inhaled deeply into the respiratory system, should be avoided.
- Avoid using products that are combustible, particularly when a large amount of the product is needed or there is a risk that it will get dispersed into the air.
- For film and television production consider adding dust effects digitally.

5.2 Product Usage

- Inform all cast and crew about the products being used, potential effects, and the necessary precautions that should be taken.
- Provide audience signage to warn of the effect being used.
- If possible mix or bind the product with a liquid medium (such as water or non-toxic binders or adhesives) to reduce the chance of it becoming airborne. If it cannot be mixed or bound in this way, then dampen the product whenever possible.
- If the product contains a range of particle sizes screen or filter out smaller particles.
- Use the minimum possible product to create the effect needed.
- Monitor and control usage and ventilation throughout the application and use to ensure that exposure is maintained at or below applicable exposure limits.
- Follow manufacturer's instructions.

Downloaded from TSP.ETA.ORG. Dowload sponsored by Prosignt Specialty Insurance.

- Eliminate or limit exposure by removing unnecessary personnel, particularly when the material is being applied.
- For set decorating, apply the product when there are few people around.
- If the usage is indoors, periodically ventilate the area.

5.3 Use PPE and Appropriate Tools

- Provide proper Personal Protective Equipment (PPE) as necessary.
- Provide appropriate tools for application of the dust effect and later clean up.

== END ==